



**ZERO KNOWS** timing is everything. With our IN-STOCK Deep Drawn Cans program, you can place an order and have it delivered to your door within days. Select from 250 sizes of our IN-STOCK Deep Drawn. For complete details about sizes, please view the catalog at [www.zerocases.com/pdf/DeepDrawn.pdf](http://www.zerocases.com/pdf/DeepDrawn.pdf)



# DEEP DRAWN

ZERO PART NUMBERS — UNTRIMMED MINIMUMS AND MAXIMUMS ARE LISTED IN MM

Z104-104B-7.50	Z28-40B-1.75	Z56-58-6.00	Z96-144-COT-.50	ZT28-54-2.31	ZT76-76A-4.25
Z107-171A-6.00	Z28-80-4.00	Z56-64-3.50	Z96-154-5.25	ZT32-48C-2.25	ZT76-96B-4.50
Z112-112-6.00	Z30-30A-2.50	Z56-72A-3.50	Z96-192-5.50	ZT32-48D-2.00	ZT80-112C-7.00
Z112-128-6.00	Z32-32A-2.25	Z56-80-3.00	Z96-96-5.00	ZT32-64D-3.00	ZT80-120A-4.00
Z112-144A-7.00	Z32-32B-3.50	Z56-96A-3.50	ZR16A-1.00	ZT34-50A-3.50	ZT80-128A-4.75
Z112-176A-7.00	Z32-36-3.75	Z59-120B-4.25	ZR26A-2.50	ZT36-108-2.25	ZT80-128B-6.00
Z112-176-COG-.50	Z32-40B-2.00	Z60-126A-3.75	ZR27A-1.63	ZT36-52-3.00	ZT80-128-COT-.31
Z113-169-9.00	Z32-40B-4.50	Z60-60A-3.75	ZR28A-2.38	ZT37-70-3.25	ZT80-176A-7.00
Z120-192-11.50	Z32-48B-2.00	Z60-72-3.75	ZR32A-2.00	ZT38-46-2.75	ZT80-98C-5.25
Z120-192-6.00	Z32-56A-3.00	Z60-80A-3.25	ZR32B-2.63	ZT38-71-3.50	ZT84-84A-6.88
Z128-128B-6.00	Z32-64A-2.50	Z61-61A-10.00	ZR35A-3.00	ZT39-79-5.50	ZT88-100-4.00
Z128-144-6.00	Z32-64B-2.00	Z64-104B-7.00	ZR39A-2.00	ZT40-102-5.00	ZT88-88B-2.50
Z128-176A-7.50	Z32-64B-COT-.37	Z64-112A-4.00	ZR40A-6.50	ZT40-80-5.88	ZT92-145A-6.00
Z128-224-7.00	Z32-83-4.00	Z64-112A-6.75	ZR48A-2.50	ZT44-52A-3.50	ZT96-128C-6.00
Z136-192A-10.00	Z34-43A-3.00	Z64-124A-6.19	ZR52A-5.25	ZT44-59-2.13	ZT96-128D-5.00
Z140-192A-8.00	Z34-68-3.00	Z64-140B-3.00	ZR56A-3.88	ZT46-64A-3.50	ZT96-160A-5.00
Z144-144A-4.00	Z36-36-2.50	Z64-144-5.00	ZR56B-2.25	ZT48-112-4.00	ZTR105-5.00
Z144-144A-8.38	Z36-48-3.00	Z64-212-4.00	ZR57A-4.00	ZT48-48C-3.00	ZTR128-10.00
Z147-212B-9.00	Z38-52A-3.38	Z64-64A-4.00	ZR59A-2.63	ZT48-60A-3.50	ZTR140-7.00
Z154-236-7.00	Z40-48-2.50	Z64-80A-3.00	ZR64A-4.50	ZT48-64D-3.13	ZTR192-7.00
Z160-166-8.75	Z40-56A-2.50	Z64-96A-3.50	ZR64B-3.50	ZT48-84C-3.00	ZTR30A-3.00
Z160-192A-9.00	Z40-64A-2.25	Z69-112A-3.50	ZR67B-4.75	ZT48-84D-3.50	ZTR31B-5.00
Z160-256A-6.00	Z40-64A-4.00	Z70-102B-6.00	ZR73A-4.75	ZT50-64A-4.25	ZTR33B-1.50
Z160-256A-9.00	Z40-64B-3.00	Z70-94-7.19	ZR74-6.50	ZT50-76A-4.25	ZTR37A-3.25
Z160-256A-CI-1.13	Z40-64-COT-.31	Z72-124-7.00	ZR81A-4.00	ZT52-64-2.50	ZTR41-2.63
Z161-209A-8.00	Z40-96A-3.25	Z72-80-4.25	ZR85-2.50	ZT52-80-5.00	ZTR42A-3.50
Z163-392B-8.00	Z41-76B-3.00	Z72-96-3.38	ZR96-5.00	ZT56-120-3.88	ZTR44A-5.00
Z16-44A-2.00	Z42-42A-4.31	Z76-192A-7.00	ZR96-6.81	ZT56-56B-2.50	ZTR48B-6.00
Z176-176B-9.00	Z44-72-2.50	Z78-104A-3.50	ZR96-COG-.63	ZT56-76-3.38	ZTR48C-3.00
Z183-209-9.00	Z48-144-3.50	Z78-104B-8.00	ZT100-100-5.00	ZT56-84A-6.50	ZTR49A-3.38
Z183-220A-6.00	Z48-160A-3.00	Z80-112A-5.00	ZT104-136B-5.50	ZT56-84B-3.50	ZTR64C-4.00
Z185-241-8.00	Z48-48A-6.00	Z80-112A-COT-.50	ZT112-200A-11.50	ZT56-84B-COG-.31	ZTR64D-6.00
Z192-288A-10.00	Z48-56A-3.25	Z80-118B-7.00	ZT128-176B-5.75	ZT64-130A-4.75	ZTR66B-5.50
Z21-30-4.00	Z48-64B-2.50	Z80-80A-5.00	ZT128-216-8.25	ZT64-80D-4.00	ZTR72B-3.25
Z21-30-COT-.37	Z48-64C-3.00	Z80-88-5.00	ZT144-192A-6.25	ZT64-88-4.38	ZTR78A-3.00
Z224-224A-9.00	Z48-72-3.00	Z80-96-5.00	ZT172-256-8.00	ZT64-96C-3.75	ZTR81B-6.75
Z240-248A-9.00	Z48-80A-3.50	Z88-128A-4.75	ZT20-52-1.75	ZT66-108A-4.63	ZTR88A-4.00
Z24-24-1.75	Z48-80B-2.00	Z91-160-5.00	ZT22-80-3.06	ZT68-68B-4.00	
Z24-30-2.50	Z48-96-3.06	Z91-160-7.00	ZT23-39-2.38	ZT68-96-4.75	
Z24-32-2.00	Z50-50A-6.00	Z96-112A-5.00	ZT24-60A-3.00	ZT72-128B-2.50	
Z26-68A-5.00	Z53-105-5.00	Z96-128B-5.00	ZT26-44-3.25	ZT72-148A-5.63	
Z28-28-2.00	Z56-56A-3.25	Z96-144-5.00	ZT28-32C-2.00	ZT76-152A-4.50	

## PART NUMBER EXAMPLE (W X L)

Z48-48A-48	Z48-48A-48-AL30	Z48-48A-48-T6	Z48-48A-48-AA
A 3.00" x 3.00" box trimmed to 3.00" made from 1100-0 alloy.	A 3.00" x 3.00" x 3.00" box, with a change in alloy to 3003-0.	A 3.00" x 3.00" x 3.00" box, with a change in alloy to 6061-0 that has been heat treated and aged to T6 condition.	A 3.00" x 3.00" x 3.00" box with nutplates installed in an 'AA' pattern.

## AVAILABLE ALLOY OPTIONS

AL11 = 1100-0    AL60 = 6061-0    AL30 = 3003-0  
 Only Alloy 6061-0 can be heat treated. When heat treatment is needed, no alloy need be specified. Please specify T4 or T6 for hardness.

No Minimum Order

Lead Time:  
5 Days ARO

In-Stock & Ready!

## IN-STOCK DEEP DRAWN ORDERING OPTIONS\*

1. Place your order by calling ZERO Toll Free **800.500.ZERO (9376)**
2. Email your order to **quickship@zerocases.com**
3. Fax your order to ZERO at **801.415.1771**

Orders received after 12:00 Noon MST will be processed the next business day.  
 \*Please reference IN-STOCK at the top of your PO to ensure prompt processing.